



www.firelite.com

July 14, 2004

DF-52384 • E-160

SD355(A)/ SD355T(A) Addressable Photoelectric Smoke Detectors

Section: Addressable Devices

GENERAL

The Fire-Lite Alarms SD355 and SD355T addressable, low-profile plug-in photoelectric detectors use a state-of-the-art photoelectric sensing chamber with communications to provide open area protection and are used exclusively with Fire-Lite's MS-9200, MS-9200UD, and MS-9600 Addressable Fire Alarm Control Panels (FACPs). The SD355T adds thermal sensors that will alarm at a fixed temperature of 135°F (57°C). Since these detectors are addressable, they will help emergency personnel quickly locate a fire during its early stages, potentially saving precious rescue time while also reducing property damage. Two LEDs on each sensor light to provide a local, visible sensor indication. Remote LED annunciator capability is available as an optional accessory (P/N RA400Z).

FEATURES

SLC loop:

- Two-wire loop connection.
- Unit uses base for wiring, detector head plugs-in.

Addressing:

- Addressable by device.
- Direct Decade 01 – 99 (MS-9200, MS-9200UD) and 01 – 159 (MS-9600) entry of address.

Architecture:

- Unique single-source, dual-chamber design to respond quickly and dependably to a broad range of fires.
- Sleek, low-profile design.
- Integral communications and built-in type identification.
- Built-in tamper-resistant feature.
- Removable cover and insect-resistant screen for simple field cleaning.

Operation:

- Withstands air velocities up to 1,500 feet-per-minute (7.6 m/sec.) without triggering a false alarm.
- Factory preset at 1.5% nominal sensitivity for panel alarm threshold level.
- Visible LED "blinks" when the unit is addressed (communicating with the fire panel) and latches on in alarm.

Mechanicals:

- Sealed against back pressure.
- Direct surface mounting or electrical box mounting.
- Mounts to: single-gang box, 3.5" (8.89 cm) or 4.0" (10.16 cm) octagonal box, or 4.0" (10.16 cm) square electrical box (using a plaster ring — included).



LISTED
S1059



MEA



California
State Fire
Marshal
7272-0075:194



APPROVED



6934pho1.jpg

SD355 with
B350LP base



6935pho1.jpg

SD355T with
B350LP base

Other system features:

- Fully coated circuit boards and superior RF/transient protection.
- 94-V0 plastic flammability rating.
- Low standby current.

Options:

- Remote LED output connection (P/N RA400Z).

APPLICATIONS

Use photoelectric detectors in life-safety applications to provide a broad range of fire-sensing capability, especially where smoldering fires are anticipated. Ionization detectors are often better than photoelectric detectors at sensing fast, flaming fires.

Fire-Lite® Alarms is a Honeywell company.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For more information, contact Fire-Lite Alarms, One Fire-Lite Place, Northford, Connecticut 06472. Phone: (800) 627-3473, Toll-Free FAX: (877) 699-4105.

ISO 9001
CERTIFIED
ENGINEERING & MANUFACTURING
QUALITY SYSTEMS

CONSTRUCTION

These detectors are constructed of off-white LEXAN®. SD355(T) plug-in, low-profile smoke detectors are designed to commercial standards and offer an attractive appearance.

LEXAN® is a registered trademark of GE Plastics, a subsidiary of General Electric Company.

INSTALLATION

SD350(T) plug-in detectors use a detachable mounting base to simplify installation, service and maintenance. Mount base on box which is at least 1.5 inches (3.81 cm) deep. Suitable boxes include:

- 4.0" (10.16 cm) square box with plaster ring.
- 4.0" (10.16 cm) octagonal box.
- 3.5" (8.89 cm) octagonal box.
- Single-gang box.

NOTE: Because of the inherent supervision provided by the SLC loop, end-of-line resistors are not required. Wiring "T-taps" or branches are permitted for Style 4 (Class B) wiring only.

OPERATION

Each SD355(T) uses one of 99 possible addresses on the MS-9200 and MS-9200UD Signaling Line Circuit (SLC), or up to 318 (159 on each loop) on the MS-9600 SLC. It responds to regular polls from the system and reports its type and status.

The SD355(T) addressable photoelectric sensor's unique unipolar chamber responds quickly and uniformly to a broad range of smoke conditions and can withstand wind gusts up to 1,500 feet-per-minute (7.6 m/sec.) without sending an alarm level signal. Because of its unipolar chamber, the SD355(T) is approximately two times more responsive than most photoelectric sensors. This makes it a more stable detector.

DETECTOR SENSITIVITY TEST

Each detector can have their sensitivity tested (required per NFPA 72, Chapter 7 on *Inspection, Testing and Maintenance*) when installed/connected to an MS-9200, MS-9200UD, or MS-9600 addressable fire alarm control panel. The results of the sensitivity test can be printed off the MS-9200, MS-9200UD, or MS-9600 for record keeping.

SPECIFICATIONS

Voltage range: 15 – 32 VDC (peak).

Standby current: 300 µA @ 24 VDC.

LED current: 6.5 mA @ 24 VDC (latched "ON").

Air velocity: 1,500 ft./min. (7.6 m/sec.) maximum.

Diameter: 6.1" (15.5 cm) installed in B350LP base.

Height: 2.1" (5.33 cm) installed in B350LP base.

Weight: 3.6 oz. (102 g).

Operating temperature range: for SD355: 0°C to 49°C (32°F to 120°F) SD350; for SD355T: 0°C to 38°C (32°F to 100°F).

Temperature: 0°C – 49°C (32°F – 120°F).

Relative humidity: 10% – 93%, non-condensing.

PRODUCT LINE INFORMATION

NOTE: "A" suffix indicates ULC-Listed model.

SD355 Addressable photoelectric detector (B350LP base included).

SD355A Same as SD355 with ULC Listing (B350LPA base included).

SD355T Same as SD355 but with **thermal** element (B350LP base included).

SD355TA Same as SD355T with ULC Listing (B350LPA base included).

RA400Z(A) Remote LED. Mounts to a single-gang box.

B350LP(A) Plug-in detector base (included). **Dimensions:** 6.1" (15.5 cm). **Mounting:** 4.0" (10.16 cm) square box with or without plastic ring, 4.0" (10.16 cm) octagonal box, 3.5" (8.89 cm) octagonal box, or single-gang box. All mounting boxes have a minimum depth of 1.5" (3.81 cm).

B224RB(A) Plug-in System Sensor **relay** detector base. **Diameter:** 6.2" (15.75 cm). **Mounting:** 4.0" (10.16 cm) square box with or without plastic ring, 4.0" (10.16 cm) octagonal box, or 3.5" (8.89 cm) octagonal box. All mounting boxes have a minimum depth of 1.5" (3.81 cm).

B224BI(A) Intelligent isolator base, isolator SLC from shorts on the loop.

B501BH(A) Plug-in System Sensor **sounder** detector base. **Diameter:** 6.0" (15.24 cm). **Mounting:** 4.0" (10.16 cm) square box with or without plastic ring. Mounting box has a minimum depth of 1.5" (3.81 cm).

B501BHT(A) Same as B501BBH(A), but includes temporal sounder.

Accessories:

RA400Z(A) Remote LED annunciator. 3 – 32 VDC. Fits U.S. single-gang electrical box. For use with B501(A) and B350LP(A) bases only.

SMK400 Surface mounting kit provides for entry of surface wiring conduit. For use with B501(A) base only.

RMK400 Recessed mounting kit. For use with B501(A) base only.

M02-04-01 Test magnet.

XR-2 Detector removal tool. Allows installation and/or removal of detector heads from bases in high ceiling applications.

XP-4 Extension pole for XR-2. Comes in three 5-ft. (1.524 m) sections.